

SEV600 MULTIMARK

TECHNICAL INFORMATION

SEV600 MultiMark

The Somerford SEV600 MultiMark is the ultimate in fully versatile truck mounted equipment for the application of sprayplastic, extrusion and profiled marking materials. The machine operation is monitored from an onboard operator station, and all pattern generation is fully computer controlled.

SPECIFICATIONS

- Available single sided or dual sided with dual steer option
- Prime mover driven power take off (PTO) system
- Material holding tank capacity of 640 litres (1280 kg)
- Bead holding vessel capacity of 114 litres (25 gallons)
- On-board independent compressor with 110v generator and aftercooler options
- Gas storage facility with optional single point safe-fill system
- Optional cab controllable hot compressed air surface preparation and drying equipment
- Optional fully electronic rear traffic control system

EXTRUSION

- Extrusion line application at 3 -12kph
- Marking widths 5 to 30cm
- Output of 160 square metres per tonne (1500 square metres per day)
- Single operation multi-width application head available

PROFILED MARKINGS

- Profiled line application at 3 -10kph
- Marking widths 10 to 30cm
- Output of 110 square metres per tonne (1000 square metres per day)
- Various profile options available

SPRAYPLASTIC

- Sprayplastic line application at 5 -16 kph
- Marking widths 5 to 50cm
- Overall output of 300 square metres per tonne (3000 square metres per day)
- Single or multiple line application

Somerford can manufacture any width application head requirement and configuration, and heads are easily interchangeable. Specification options can include on-board water storage for line cooling, bulk gas oil storage tank, rear underbody application head and tool storage, integrated keyless ignition system, LED lighting and safety vehicle livery options amongst others.